O·P·I

# SAFETY DATA SHEET

Page 1 of 6 **SDS-365** 

Drop	Tod to OSHA ACC ANS	I NOUSC WHMIS	CHE 8 1272/200	9/EC Standarda		ene	Revision: 1	1	ene r	Povision	n Doto:	4/12/2018
repa	ared to OSHA, ACC, ANS	, NORSC, WHINIS,	, GHS & 12121200	o/EC Standards		303	s Revision. I	.1	2D2 F	Revision	i Date.	4/12/2010
			BBBBII	T 0 0011	D 4 4 13 7	IDENITI		<u> </u>				
		<u> </u>	PRODUC	I & COM	PANY	IDENII	FICA II	ON				
1.1	Product Name:	OPI INF	INITE SHI	<b>NE ProSt</b>	ay GL0	oss						
.2	Chemical Name:	Solvent Mixt	ture									
.3	Synonyms:	OPI Infinite	OPI Infinite Shine ProStay Gloss – Top Coat									
.4	Trade Names:	IS T31										
.5	Product Use:	Cosmetic Us	se Only									
.6	Distributor's Name:	OPI Product	ts, Inc.									
.7	Distributor's Address:	4500 Park C	Granada Blvd, C	alabasas, CA 9	91302 USA	١						
.8	Emergency Phone:	CHEMTR	EC: +1 (703	) 527-3887 /	/ +1 (800	) 424-93	00 (CCN	16377)				
.9	Business Phone / Fax:	Tel: +1 (818			•		•					
			,									
			2. H	AZARDS	IDENT	FICATI	ON					
.1	Hazard Identification:		t is classified as				as DANGE	ROUS GO	OODS	accord	ling to	the classificat
			OHSC: 1008 (20	•	•					01/11		
			HIGHLY FLAM ATION. AVOID						RGIC	SKIN	REAC	TION. CAUS
2	Label Elements:	Classification	<u>n</u> : Flam. Liq. 2;	Skin Sens. 1A;	Eye Irrit. 2	2B						
.3	Other Warnings:	skin reaction Precautiona Smoking. F static dischaskin areas t should not t protection. P302+P352 continuously continue rin: P321 – For contaminate chemical, or – Dispose of	ements (H): H2:  n. H320 - Caus  ry Statements ( 2233 - Keep co  arge. P261 - A  thoroughly with  be allowed out  P280 - Wear  - IF ON SKIN:  with water for  sing. P333+P3  specific first aid  d clothing befor  foam for extinct	es eye irritation P): P210 – Kee Intainer tightly Avoid breathing soap and wat of the workpla I protective gl Wash with so several minute I skin irri I treatment (Se re reuse. P37 Ition. P403+P2 iner to a licens	ep away fr closed. F g fume/gas er after ha ce. P280 oves/prote ap and wa es. Remov ritation or dee Section 0+P378 -	om heat/sp 243 – Tak s/mist/vapou andling. P2 – Wear pructive clothi ater. P3054 ee contact luar rash occu 4 of this S In case of e in a well-v	arks/open to precaution arks/open to precaution arks/spray. 1272 — Controller Congleye propersis if programmers — Get monafety Data fire, CO <sub>2</sub> , I prentilated p	flame/hot phary mea P264 – Vaminated byes/eye potection/fa 8 – IF IN eseent and pharedical ac Sheet). Halon (if place. Kee	surface asures Vash e work orotecti ce pro EYES: I easy Ivice/at P363 - permitte ep cool	es – N agains expose clothin ion/fac otection : Rins to do ttention – Was ed), di	o o st d g e e n. e e - n. h ry	
0	Other Warnings.	KEEP OUT	OF REACH OF	CHILDREN.								
			OMBOOIT	10110111	00501			TION				
		3 C	OMPOSIT	IUN & IN	GKEDI	ENI INI	FUKMA	NUILI				
		<u> </u>	<del></del>	1							•	
		<u></u>						XPOSURE L	IMITS IN		g/m³)	
		0. 0				ACGIH	NO	HSC	IMITS IN	OSHA	g/m³)	
	CAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%		NO pi				g/m³)	OTHER

3. COMPOSITION & INGREDIENT INFORMATION													
					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	om		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ETHYL ACETATE	141-78-6	AH5425000	205-500-4	30-60	400	400	200	400	NF	NA	NA	2000	400 TWA
	Flam. Liq. 2; Ey	e Irrit. 2; STOT S	SE 3; H225, H31	9, H336									
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	10-30	150	200	150	200	NF	200	200	1700	100 NIOSH
BOTTE AGETATE	Flam. Liq. 3; S	OT SE 3; H226,	H336										
CELLULOSE ACETATE BUTYRATE	9004-36-8	NA	NA	10-30	NA	NA	NF	NF	NF	NA	NA	NA	
CEEEOLOSE ACETATE BOTTKATE													
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	5.0-20	400	500	400	500	NF	400	500	2000	400 TWA
ISOT NOT TE ALGOTIGE	Flam. Liq. 2; Skin Irrit. 3; Eye Irrit. 2A; STOT SE 3; H225, H316, H319												
ACETYL TRIBUTYL CITRATE	77-90-7	NA	201-067-0	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	
ACETTE TRIBOTTE CITRATE	Flam. Gas 1; M	uta. 1B; Carc. 1E	3; H220, H340, F	l350									
HEA/IPDI ISOCYANURATE	NA	NA	NA	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	
TRIMER/PG CROSSPOLYMER													
HYDROXYETHYL	NA	NA	NA	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	
ACRYLATE/IPDI/PPG-15													
GLYCERYL ETHER COPOLYMER								,	,				
ETHYTL TRIMETHYLBENZOYL	84434-11-7	NA	282-810-6	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
PHENYL PHOSPHINATE	70000 00 4	la i a	1070 057 5	0.4.4.0	N1A					N1A	NIA.	NIA.	
DI-HEMA TRIMETHYLHEXYL	72869-86-4	NA	276-957-5	0.1-1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DICARBAMATE	Skin Sens.1; H							,	,				
ISOSORBIDE	1215036-04-6	NA	NA	0.1-1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DICAPRYLATE/CAPRATE		1	1	1									
TRIMETHYLPENTANEDIYL DIBENZOATE	68052-23-3	NA	268-316-3	0.0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60725 (VIOLET 2)	81-48-1	CB7700000	201-353-5	0.0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	
(													

### SAFETY DATA SHEET

Page 2 of 6

**SDS-365** Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 4/12/2018 4. FIRST AID MEASURES 4 1 First Aid: If ingested, do not induce vomiting. Drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, Ingestion: continue to offer plenty of water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time and amount of the substance that was swallowed. If product is in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and Eyes: close eyelid(s) to ensure thorough irrigation. If problem persists, consult a physician. Skin: If redness, dryness or other signs of irritation to the skin develop, wash affected skin areas with plenty of warm water and soap. If irritation persists, consult a physician. Inhalation: Remove victim to fresh air at once. 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: depression Irritating to eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Eyes: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. Skin: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory Inhalation: system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea) Symptoms of Overexposure: Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. 4.3 Overexposure in eyes may cause redness, itching and watering. Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause 4.4 Acute Health Effects: drowsiness, dizziness, headaches and nausea. No chronic health effects are known, although symptoms and discomfort may occur for several days following 4.5 Chronic Health Effects: overexposure. 4.6 Target Organs: Eyes, Skin, Respiratory System. Medical Conditions HEALTH 4.7 None known. Aggravated by Exposure: **FLAMMABILITY** 3 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, 5.1 Fire & Explosion Hazards: sparks & open flame. Keep container closed. CO<sub>2</sub>, Halon (if permitted), Dry Chemical, Foam, as authorized. 5.2 Extinguishing Methods: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily 5.3 Firefighting Procedures: and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container 7.2 Storage & Handling: closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). 7.3 Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may

contain residual amounts of this product; therefore, empty containers should be handled with care.

Page 3 of 6  $0.9 \cdot 1$ SAFETY DATA SHEET SDS-365 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 4/12/2018 8. EXPOSURE CONTROLS & PERSONAL PROTECTION OTHER Exposure Limits: NOHSC OSHA ppm (mg/m<sup>3</sup>) ES-CHEMICAL NAME(S) ETHYL ACETATE STE TWA PEL STEI IDLH 400 400 200 400 NF NA NA 2000 400 TWA BUTYL ACETATE NF 1700 150 TWA 150 200 150 200 200 200 ISOPROPYL ALCOHOL 400 500 400 500 NF 400 500 400 TWA 2000 8.2 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, EU member states, or Australia. 8.4 Eye Protection: Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166. 8.5 Hand Protection: If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the EU member states. Body Protection: 8.6 No special body protection is required under typical circumstances of use and handling. necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Viscous liquid, various colors Odor Ester (fruity) odor 9.2 Odor Threshold: ND 9.3 9.4 pH: NA Melting Point/Freezing Point: 9.5 NA Initial Boiling Point/Boiling 9.6 NA Range: Flashpoint - 4 °C (24.8 °F) estimated 9.7 Upper/Lower Flammability 9.8 NA Limits: Vapor Pressure: 9.9 NA Vapor Density: 9 10 ND Relative Density: 9.11 ND Solubility: 9.12 Insoluble Partition Coefficient (log Pow): ND 9 13 Autoignition Temperature 9.14 NA Decomposition Temperature: ND 9.15 Viscosity: 9.16 > 1.200 cPs Other Information: 9 17 NA 10. STABILITY & REACTIVITY 10.1 This product is stable under ambient conditions when stored properly (See Section 7, Storage and Handling) Hazardous Decomposition 10.2 If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and Products: carbon oxide gasses (e.g., CO, CO<sub>2</sub>) May occur, if exposed to extremely high temperatures. 10.3 Hazardous Polymerization Open flames, sparks, high heat and direct sunlight. This product is incompatible with strong oxidizers (e.g., peroxides, 10.4 Conditions to Avoid: superoxides), strong acids (e.g., hydrochloric or muriatic acids), strong bases (e.g., lye, potassium hydroxide). 10.5 Incompatible Substances: None known. 11. TOXICOLOGICAL INFORMATION Absorption: YES Routes of Entry: 11.1 Ingestion: YES The product has NOT been tested on animals to obtain toxicological data. There are toxicology data for the components Toxicity Data: of this product, which are found in the scientific literature. This data has not been presented in this document 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 This product contains Isopropyl Alcohol, which is not carcinogenic to humans but is listed as a Group 3 carcinogen by 11.5 Suspected Carcinogen: the IARC This product is not reported to produce reproductive toxicity in humans 11.6 Reproductive Toxicity: Mutagenicity: This product is not reported to produce mutagenic effects in humans Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to produce teratogenic effects in humans. This product is not reported to produce reproductive effects in humans. Reproductive Toxicity: Irritancy of Product: See Section 4.3 11.8 Biological Exposure Indices: NE

Treat symptomatically.

11.9

Physician Recommendations:

 $O \cdot P \cdot I$ 

# **SAFETY DATA SHEET**

Page 4 of 6 **SDS-365** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 4/12/2018

	ileu to OSHA, ACO, ANSI, N	
		12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: <u>Ethyl Acetate</u> : Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not applicated to be considered. This compound can be removed from contaminated environments from valetilization, and
		anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.  Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H <sub>2</sub> O at 25°C (77°F). Bioconcentration Factor = 4-14.
		Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.  Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation
		of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large release of this product may be harmful or fatal to overexposed aquatic life.
		13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:	Dispose of in accordance with federal, state and local regulations.
13.2	Special Considerations:	U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)
		14. TRANSPORTATION INFORMATION
The b	basic description (ID Num riptive information may be 49 CFR (GND):	nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.  UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L); or
	,	CONSUMER COMMODITY, ORM-D – until 01/01/2021
14.2	IATA (AIR):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 0.5 L); or
		ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L)
14.3	IMDG (OCN):  TDGR (Canadian GND):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)
14.4	ADR/RID (EU):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)
	, ,	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)
14.6	SCT (MEXICO):	UN1263, PRODUCTOS PARA PINTURA, 3, II, (CANT. LTDA., (IP VOL ≤ 1.0 L)
14.7	ADGR (AUS):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)
		15. REGULATORY INFORMATION
15.1	SARA Reporting Requirements:	This product contains <u>Isopropanol</u> , a substance subject to SARA Title III, Section 313 reporting requirements. This product contains <u>Ethyl Acetate</u> , a substance that is subject to SARA Title III, Section 304 reporting.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory or are otherwise exempt.
15.4	CERCLA Reportable Quantity (RQ):	Ethyl Acetate: 2,270 kg (5,000 lbs); Butyl Acetate: 2,270 kg (5,000 lbs)
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)
15.7	State Regulatory Information:	Butyl Acetate is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI).  Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA.
		Isopropanol is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA.  No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information, go to www.P65warnings.ca.gov.

 $0.9 \cdot 1$ 

### **SAFETY DATA SHEET**

Page 5 of 6 SDS-365

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 4/12/2018 16. OTHER INFORMATION 16.1 Other Information: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. Keep away from heat/sparks/open flame/hot surfaces - No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/gas/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. OPI Products, Inc. 16.4 Prepared for: 4500 Park Granada Blvd Calabasas, CA 91302 USA Tel: +1 (818) 999-5112 http://www.opi.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 **ShipMate** Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

## **SAFETY DATA SHEET**

Page 6 of 6 **SDS-365** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision Date: 4/12/2018

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		



#### PERSONAL PROTECTION RATINGS:

Α			
В			
С		型	
D		西	
Е			
F		型	

















Dust & Vapor Half-Mask Respirator **Full Face Respirator** 

**Full Face** Respirator

**a** Airline Hood/Mask or SCBA

#### OTHER STANDARD ABBREVIATIONS:


Irritant
IIIIdiil
Not Available
No Results
Not Determined
Not Established
Not Found
Self-Contained Breathing Apparatus
Sensitization
Specific Target Organ Toxicity – Repeat Exposure
Specific Target Organ Toxicity – Single Exposure
1 1 1

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI'	FLAMMABILITY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

#### **HAZARD RATINGS:**

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	4 Extreme Hazard	
ACD	D Acidic	
ALK	Alkaline	
COR	Corrosive	
W	Use No Water	
OX Oxidizer		
TREFOIL	Radioactive	



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>Io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(*)</b>	<b>(2)</b>	(3)	$\odot$	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compress ed	Flammabl e	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			$\Diamond$		¥2>
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment