

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

| | | | |
|----------------------|---|--------------|-----------|
| PRODUCT NAME: | Clean + Easy Lavender Moisture Absorbent Powder | DATE: | 1/27/2004 |
| FORMULA: | 30-1921 | REV. | NEW |

Section 1. Material Identification and Information**Hazardous Ingredients:**

| Component | CAS # | % | TOXICOLOGICAL DATA |
|-----------|------------|-----|---|
| Talc | 14807-96-6 | 99% | OSHA PEL/TWA: 2.0mg/cu.m. ACGIH TLV/TWA: 2.0mg/cu.m. |

Section 2. Physical / Chemical Characteristics

| | | | |
|-----------------------------|------------------------|--------------------------|-----|
| Boiling Point: | N/A | Specific Gravity: | N/A |
| Vapor Pressure: | N/A | (@ 25°C) | |
| (mm Hg and Temperature) | | Melting Point: | N/A |
| Vapor Density: | N/A | Evaporation Rate: | N/A |
| (Air = 1) | | Water Reactive: | N/A |
| Solubility in Water: | Soluble | | |
| Appearance: | Very Fine White Powder | | |
| Odor: | Odorless | | |

Section 3. Fire and Explosion Hazard Data

| | |
|--|---|
| Flash Point and Method Used: | N/A |
| Auto-Ignition Temperature: | N/A |
| Flammability Limits in Air % by Volume: | LEL: N/A UEL: N/A |
| Extinguisher Media: | Material is non-combustible. Follow fire extinguishing procedures for surrounding combustibles. |
| Special Fire Fighting Procedures: | Material is non-combustible. Follow fire fighting procedures for surrounding materials. |
| Unusual Fire and Explosion Hazards: | Material is non-combustible and is not an explosion hazard. |

Section 4. Reactivity Hazard Data

Stability: ☒ Stable ☐ Unstable

Conditions to Avoid: Water and moisture.

Incompatibility (Materials to Avoid):
None in designed use.

Hazardous Decomposition:
None Known

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Clean + Easy Lavender Moisture Absorbent Powder **DATE:** 1/27/2004

FORMULA: 30-1921 **REV.** NEW

Hazardous Polymerization:

☐ May Occur ☒ Will Not Occur

Section 5. Health Hazard Data**Primary Routes of Entry:**

☒ Inhalation ☒ Skin Absorption ☒ Ingestion ☒ Eye Contact

Carcinogen Listed In:

☐ NTP ☐ IARC Monograph ☐ OSHA ☒ Not Listed

Emergency Overview:

Dust may cause mechanical irritation to eyes and respiratory tract.

Health Hazards: Acute: Inhalation - Inhalation of dusts may cause sneezing, coughing, and nose irritation.
Skin Contact - The abrasiveness of talc may cause skin irritation.
Eye Contact - Abrasion may cause eye irritation.
Ingestion - May cause mild irritation of gastrointestinal tract.
Chronic: Inhalation - Long-term excessive exposures may cause talcosis, a pulmonary fibrosis which may lead to severe and permanent damage to the lung - possibly resulting in disability or death.

Signs and Symptoms of Exposure:

Eye Contact: Mild irritation.
Skin Contact: Dryness and/or mild irritation.
Inhalation: Excessive sneezing or coughing.
Ingestion: Mild irritation.

Medical Conditions Generally Aggravated by Exposure:

Pre-existing chronic respiratory, skin, or eye diseases.

Emergency First Aid Procedures:

Eye Contact: Flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.
Skin Contact: Wash from skin with mild soap and water.
Inhalation: Remove exposed person to fresh air. If symptoms such as excessive sneezing or coughing develop, seek medical attention.
Ingestion: Ingestion should not cause significant health problems. If this material is ingested, and if the person is conscious, give large quantities of water to induce vomiting. Get medical attention.
Note to Physician: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than talc may have occurred.

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

| | | | |
|----------------------|--|--------------|------------------|
| PRODUCT NAME: | Clean + Easy Lavender Moisture Absorbent Powder | DATE: | 1/27/2004 |
| FORMULA: | 30-1921 | REV. | NEW |

Section 6. Control and Protective Measures**Respiratory Protections (Specific Type):**

When established airborne exposure limits are surpassed, wear NIOSH/MSHA approved respiratory equipment for dust. Determine the appropriate type of equipment for specific applications by consulting the respiratory manufacturer. Observe the respiratory use limitations specified by NIOSH/MSHA or the manufacturer. In addition, respiratory protection programs must comply with 29 CFR 1910.134. Engineering or administrative controls should be implemented to reduce exposure.

Protective Gloves: Leather or impervious gloves.

Eye Protection: Safety glasses equipped with side shields or dust tight goggles.

Ventilation to be Used:

Provide adequate exhaust ventilation to meet exposure limit requirements. An exhaust filter

Other Protective Clothing and Equipment:

Wear long sleeve clothing to prevent skin contact.

Hygienic Work Practices:

Good Manufacturing Practices.

Section 7. Precautions for Safe Handling and Use / Leak Procedures**Steps to be Taken if Material is Spilled or Released:**

Provide adequate ventilation. Clean-up personnel should use protective equipment to reduce eye contact, inhalation of dust and prolonged skin contact. Use vacuum suction with HEPA filters to clean up spilled material. Use wet sweeping or a dust suppressant where sweeping is necessary. Personal safety, handling and exposure recommendations described elsewhere in this data sheet apply to exposure during clean up or spilled material and must be followed.

Waste Disposal Methods:

If this material becomes a waste, it does not meet the criteria of a hazardous waste as defined under the resource conservation and recovery act (RCRA) 40 CFR 261, since it does not have the characteristics of subpart C, nor is it listed under subpart D. State or local hazardous waste regulations may apply if they are different from the federal regulations. The user should be aware that combining this material with another may alter this classification.

Precautions to be taken in Handling and Storing:

Avoid damaging container. Store to minimize or avoid dust generation. Store in clean, dry locations.

Other Precautions and/or Special Hazards:

None

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

| | | | |
|----------------------|--|--------------|------------------|
| PRODUCT NAME: | Clean + Easy Lavender Moisture Absorbent Powder | DATE: | 1/27/2004 |
| FORMULA: | 30-1921 | REV. | NEW |

Section 8. Regulatory Information

All regulations below apply to the Talc ingredient.

OSHA Hazard Communication Status:

This product is considered hazardous under the criteria of the federal OSHA hazard communication standard 29 CFR 1910.1200.

Asbestiform Mineral Content:

No asbestiform minerals have been detected in this product.

TSCA Status:

All ingredients in this product are either naturally occurring and exempt from reporting or are included in EPA's toxic substance control act inventory of chemical substances.

SARA 311/312 Hazard Class:

This product contains substances regulated under 29 CFR 1910.1200 (OSHA Hazard Communication) as immediate (acute) health hazards.

Tariff Classification:

TALC 2526.20

"Coneg" Model Legislation:

There are no cadmium, hexavalent chromium, lead, or mercury additives. These products incidentally contain only trace amounts of these metals, far below the 100ppm threshold level.

International Chemical Lists:

ACQIN (Australia)
MITI (Japan)
LECS (Korea)
EINECS (Europe)
DSL (Canada)

Clear Air Act Components:

This product does not contain nor has it come into contact with ozone depleting chemicals. Furthermore, no ozone depleting chemicals were used in the manufacturing process.

WHMIS Classification:

Class D, Division 2, Subdivision B.

California Proposition 65:

Talc may contain the following proposition 65 regulated chemicals in the following typical amounts:

| | |
|--------------------|--------------|
| Arsenic | 2ppm |
| Cadmium | 2ppm |
| Chromium | 0.5ppm |
| Mercury | 0.5ppm |
| Lead | 5ppm |
| Crystalline Silica | 1.0% Maximum |

These chemicals are present as impurities and occur as a result of their natural presence in the ore from which the talc is produced.